

Solventborne

Product name
ACRYDIC AP-1016-HV

Description

ACRYDIC AP-1016-HV is a solventborne thermoplastic acrylic resin for 1K lacquer coatings. ACRYDIC AP-1016-HV has compatibility with NC and CAB and fast drying properties. It is recommended for automotive refinishing and metal coatings.

Applications

Automotive refinishing.
Metal coatings.

Key features

Compatible with NC and CAB.
Fast drying.
Hardness.
High gloss.
Gasoline resistance.
Weather resistance.

Characteristics

	ACRYDIC AP-1016-HV
Appearance	Clear liquid
Solids content, weight %	51.5 - 53.5
Viscosity, Gardner 25°C	Y - Z2
Color, Gardner	1 max.
Acid value, mgKOH/ml	3.0 - 5.0
Solvent	Toluene / Butyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC AP-1016-HV.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210604

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.