

**Solventborne**

**Product name**  
**ACRYDIC AU-7202**

**Description**

ACRYDIC AU-7202 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. ACRYDIC AU-7202 has excellent adhesion to plastics substrates and self-healing properties. It is recommended for consumer electronics and automotive interior coatings.

**Applications**

Consumer electronics.  
Automotive interior mono and top coatings.

**Key features**

Adhesion to plastics like ABS, PC and PC/ABS.  
Chemical resistance.  
Self-healing properties.  
BTX-free.

**Characteristics**

	<b>ACRYDIC AU-7202</b>
<b>Appearance</b>	Light yellow turbid liquid
<b>Solids content, weight %</b>	49.0 - 51.0
<b>Viscosity, Gardner 25°C</b>	D - J
<b>Color, Gardner</b>	2 max.
<b>Acid value on solution, mgKOH/g</b>	3 max.
<b>OH value on solution, mgKOH/g</b>	35.0 - 41.0
<b>Solvent</b>	Butyl acetate

**Storage**

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ACRYDIC AU-7202.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.