

**Solventborne**

**Product name**  
**ACRYDIC A-416-70SZ**

**Description**

ACRYDIC A-416-70SZ is a solventborne OH functional acrylic resin to use in combination with amino resins for stoving enamels. ACRYDIC A-416-70SZ has excellent adhesion to metal substrates, high gloss and hardness, excellent salt spray resistance and it is high solids. It is recommended for home appliances and industrial coatings.

**Applications**

Home appliances.  
Industrial coatings.

**Key features**

Adhesion to metal substrates.  
Appearance.  
Abrasion resistance.

**Characteristics**

	<b>ACRYDIC A-416-70SZ</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	69.0 - 71.0
<b>Viscosity, Gardner 25°C</b>	W - Z
<b>Color, Gardner</b>	2.0 max.
<b>Acid value on solution, mgKOH/g</b>	5.0 - 7.0
<b>Solvent</b>	Solvesso-100 / n-Butanol

**Storage**

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ACRYDIC A-416-70SZ.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

211101

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.