



Color & Comfort

TECHNICAL DATA SHEET

Solventborne

High solids

Product name

ACRYDIC A-9585-BA

Description

ACRYDIC A-9585-BA is an epoxy silane hardener to use in combination with solventborne moisture curing silicone acrylic resins for 2K coatings. ACRYDIC A-9585-BA has excellent hardness. It is recommended for wood and plastic coatings.

Applications

Wood coatings.
Plastic coatings.

Key features

Hardness.
BTX free.

Characteristics

	ACRYDIC A-9585-BA
Appearance	Clear liquid
Solids content, weight %	80.0
Color, Gardner	1 max.
Epoxy equivalent weight, g/eq	530 - 585
Solvent	Isobutyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC A-9585-BA.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210609

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC Corporation

For more information: <https://www.dic-global.com/en/products/coating.html>