

TECHNICAL DATA SHEET

Solventborne

High solids

Product name

ACRYDIC AC-3510-IM

Description

ACRYDIC AC-3510-IM is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings.

ACRYDIC AC-3510-IM has excellent appearance and high gloss. It is recommended for automotive refinishing or motorcycle finishes top clear or solid color coatings.

Applications

Automotive refinishing.

Motorcycle finishes.

Key features

High-solids.

Appearance.

High gloss.

Hardness.

Chemical resistance.

Weather resistance.

Recoatibility.

Characteristics

	ACRYDIC AC-3510-IM
Appearance	Clear Liquid
Solids Content, weight %	69.0 - 71.0
Viscosity, Gardner 25°C	Z3 - Z5
Color, Gardner	1 max.
Acid Value on solution, mgKOH/g	7.5 - 9.5
OH Value on solution, mgKOH/g	57 - 67
Specific Gravity, 25°C	1.02 - 1.04
Solvent	Xylene / Butyl acetate

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for ACRYDIC AC-3510-IM.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210604

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC Corporation

For more information: <https://www.dic-global.com/en/products/coating.html>