

Solventborne

Product name
ACRYDIC AC-3661

Description

ACRYDIC AC-3661 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. ACRYDIC AC-3661 has fast drying properties and high gloss. It is recommended for automotive refinishing and motorcycle finishes clear topcoats.

Applications

Automotive refinishing.
Motorcycle finishes.
Metal, plastic and wood coatings.

Key features

Fast drying.
High gloss.
Adhesion.

Characteristics

	ACRYDIC AC-3661
Appearance	Clear Liquid
Solids content, weight %	59.0 - 61.0
Viscosity, Gardner 25°C	W - Z
Color, Gardner	1 max.
Acid Value on solution, mgKOH/g	3 max.
OH Value on solution, mgKOH/g	32 - 40
OH Value on solids, mgKOH/g	53 - 67
OH content on solution, %	Approx. 1.1
OH content on solids, %	1.6 - 2.0
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for ACRYDIC AC-3661.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.