TECHNICAL DATA SHEET



Solventborne

Product name ACRYDIC AL-201

Description

ACRYDIC AL-201 is a solventborne thermoplastic acrylic resin for 1K lacquer coatings. ACRYDIC AL-201 has excellent adhesion to PP substrates and gasoline resistance. It is recommended for 1K PP primer coatings.

Applications

PP Primer coatings.

Key features

Adhesion to PP substrates. Gasoline resistance when tested with topcoat.

Characteristics

	ACRYDIC AL-201	
Appearance	Yellow turbid liquid	
Solids content, weight %	44.0 - 46.0	
Viscosity, Gardner 25°C	V - X	
Color, Gardner	8 max.	
Acid value on solution, mgKOH/g	0.5 - 2.0	
Solvent	Toluene	

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC AL-201. Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220322

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC Corporation

For more information: https://www.dic-global.com/en/products/coating.html