

Solventborne

Product name
ACRYDIC AU-7213

Description

ACRYDIC AU-7213 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. ACRYDIC AU-7213 has excellent adhesion to plastics substrates, metallic pigment orientation, water resistance and workability. It is recommended as primer or topcoat.

Applications

Consumer electronics.
Home appliances.
Plastic coatings.
Automotive interior coatings.

Key features

Adhesion on plastic substrates.
Water resistance.
Applicable to low VOC formulation.
Can be used as primer or topcoat.

Characteristics

	ACRYDIC AU-7213
Appearance	Clear liquid
Solids content, weight %	54.0 - 56.0
Viscosity, Gardner 25°C	U - Y
Color, Gardner	1 max.
Acid value on solution, mgKOH/g	1.0 - 3.0
OH value on solution, mgKOH/g	12.0 - 18.0
Solvent	n-Propyl acetate

Storage

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC AU-7213.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

211101

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.