

Solventborne

Product name
ACRYDIC BK-8204

Description

ACRYDIC BK-8204 is a solventborne OH functional acrylic resin to use in combination with amino resins for stoving enamels, it can be used for solventborne coatings and waterborne coatings. ACRYDIC BK-8204 has high gloss, fullness, excellent water resistance and flexibility. It is recommended for industrial coatings and automotive coatings.

Applications

Industrial coatings.
Automotive coatings.

Key features

High gloss.
Fullness.
Water resistance.
Flexibility.

Characteristics

	ACRYDIC BK-8204
Appearance	Clear liquid
Solids content, weight %	68.0 - 71.0
Viscosity, Gardner 25°C	V - Z
Color, Gardner	1.0 max.
Acid value on solution, mgKOH/g	37.0 - 47.0
Solvent	Butyl cellosolve, n-Butanol, Propylene glycol methyl ether

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC BK-8204.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

231111

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.