

**Solventborne**

**Product name**  
**ACRYDIC LA-9006**

**Description**

ACRYDIC LA-9006 is a solventborne thermoplastic acrylic resin for 1K lacquer coatings. ACRYDIC LA-9006 has excellent adhesion to plastic substrates and hardness. It is recommended for home appliances plastic coatings.

**Applications**

Plastic coatings.  
Metallic and clear coatings.

**Key features**

Hardness.  
Alcohol resistance.  
Water resistance.  
Biobased acrylic resin (biomass content 21%)  
BTX free.

**Characteristics**

	<b>ACRYDIC LA-9006</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	39.0 - 41.0
<b>Viscosity, Gardner 25°C</b>	U - Y
<b>Color, Gardner</b>	1 max.
<b>Acid value on solution, mgKOH/g</b>	1 max.
<b>Solvent</b>	Isobutyl acetate / Isobutanol / Ethyl acetate

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ACRYDIC LA-9006.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210623

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.