

**Solventborne**

**Product name**  
**ACRYDIC SD-44-LV**

**Description**

ACRYDIC SD-44-LV is a solventborne OH functional acrylic resin to use in combination with amino resins for stoving enamels. ACRYDIC SD-44-LV has excellent flexibility and pasteurization and sterilization resistance. It is recommended for exterior can coatings.

**Applications**

Exterior can coatings.  
Industrial metal coatings.

**Key features**

High gloss.  
Intercoat adhesion between printing ink and white base.  
Flexibility.  
Weather resistance.  
Pasteurization and sterilization resistance.

**Characteristics**

	<b>ACRYDIC SD-44-LV</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	49.0 - 51.0
<b>Viscosity, Gardner 25°C</b>	V - X
<b>Color, Gardner</b>	3 max.
<b>Acid value on solution, mgKOH/g</b>	2.0 - 5.0
<b>Solvent</b>	Solvesso-150

**Storage**

Store in a cool, dry, and well-ventilated place at temperatures between 15°C - 45°C.

**Safe handling note**

Refer to SDS for ACRYDIC SD-44-LV.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.