

**Solventborne**

**Product name**

**ACRYDIC WFU-289**

**Description**

ACRYDIC WFU-289 is a solventborne OH functional acrylic resin to use in combination with polyisocyanate for 2K polyurethane coatings. ACRYDIC WFU-289 has excellent chemical resistance and adhesion to several plastic substrates. It is recommended for automotive interior coatings.

**Applications**

Automotive interior coatings.  
Plastic coatings.

**Key features**

Adhesion to plastics substrates.  
Chemical resistance.  
Sunscreen lotion resistance.  
BTX free.

**Characteristics**

	<b>ACRYDIC WFU-289</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	49.0 - 51.0
<b>Viscosity, Gardner 25°C</b>	Z1 - Z5
<b>Color, Gardner</b>	1 max.
<b>Acid value on solution, mgKOH/g</b>	2.0 - 4.0
<b>OH value on solution, mgKOH/g</b>	17.0 - 23.0
<b>Solvent</b>	Isobutyl acetate

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ACRYDIC WFU-289.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.