

Solventborne

Product name
ACRYDIC WNL-200

Description

ACRYDIC WNL-200 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. ACRYDIC WNL-200 has excellent pigment dispersibility. It is recommended for automotive interior, plastic coatings and consumer electronics coatings.

Applications

Automotive interior coatings.
Consumer electronics.

Key features

BTX free.
Pigment dispersibility.

Characteristics

	ACRYDIC WNL-200
Appearance	Clear liquid
Solids content, weight %	49.0 - 51.0
Viscosity, Gardner 25°C	Y - Z3
Color, Gardner	2 max.
Acid value on solution, mgKOH/g	1.0 - 3.0
OH value on solution, mgKOH/g	17.0 - 23.0
Solvent	Butyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ACRYDIC WNL-200.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210609

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.