

Solventborne

Product name

ACRYDIC WNL-379

Description

ACRYDIC WNL-379 is a solventborne thermoplastic acrylic resin for 1K lacquer coatings. ACRYDIC WNL-379 has excellent chemical resistance. It is recommended for automotive interior coatings.

Applications

Automotive interior coatings.
Home appliances.
Motorcycle finishes.

Key features

Chemical resistance.
Metallic pigment orientation.
Adhesion to plastics like ABS, PC and PC/ABS.
BTX free.

Characteristics

	ACRYDIC WNL-379
Appearance	Clear liquid
Solids content, %	39.0 - 41.0
Viscosity, Gardner 25°C	P - W
Color, Gardner	1 max.
Acid value on solution, mgKOH/g	0.5 - 2.0
Solvent	Methyl isobutyl ketone / Isobutanol / Ethyl acetate
Appearance	Clear liquid

Storage

Store in a cool, dry, well-ventilated place at temperatures between 15 - 40°C.

Safe handling note

Refer to SDS for ACRYDIC WNL-379.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220527

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.