

**Non-solvent**

**Product name**

**ALUKIDIR EL-8001**

**Description**

ALUKIDIR EL-8001 is a solvent free long oil alkyd resin to use with metal carboxylates driers for air drying coatings. It is recommended for architectural coatings.

**Applications**

Architectural coatings.

**Key features**

Solvent free.

**Characteristics**

	<b>ALUKIDIR EL-8001</b>
<b>Appearance</b>	Light yellow clear liquid
<b>Solids content, weight %</b>	100
<b>Viscosity, mPa s25°C</b>	3000 - 3500
<b>Color, Gardner</b>	11 max.
<b>Acid value on solid, mgKOH/g</b>	15 max.
<b>Type of oil</b>	Soybean
<b>Oil length, %</b>	80

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ALUKIDIR EL-8001.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210609

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.