

Solventborne

Product name
ALUKIDIR J-524-70-BA

Description

ALUKIDIR J-524-70-BA is a solventborne short oil alkyd resin that can be used in combination with nitrocellulose as a 1K lacquer or in combination with amino resins for stoving enamels. ALUKIDIR J-524-70-BA has high gloss and hardness, chemical resistance and good color retention properties. It is recommended for industrial coatings.

Applications

General industrial coatings.

Key features

- Hardness.
- Color retention.
- High gloss.
- Chemical resistance.
- BTX-free.

Characteristics

	ALUKIDIR J-524-70-BA
Appearance	Clear liquid
Solids content, weight %	69.0 - 71.0
Viscosity, Gardner 25°C	Z1 - Z3
Color, Gardner	4 max.
Acid value on solution, mgKOH/g	9 max.
Type of oil	Coconut
Oil length, %	35
Solvent	Butyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for ALUKIDIR J-524-70-BA.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.