

**Solventborne**

**Product name**  
**ALUKIDIR M-2168-50**

**Description**

ALUKIDIR M-2168-50 is a solventborne phenolic modified medium oil alkyd resin to use with metal carboxylate driers for air drying coatings. ALUKIDIR M-2168-50 has fast drying and excellent anti-corrosion properties. It is recommended for metal coatings primer.

**Applications**

Metal coatings primer.

**Key features**

- Fast drying.
- Hardness.
- Anti-corrosion.
- Heat resistance.
- Recoatibility.

**Characteristics**

	<b>ALUKIDIR M-2168-50</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	49.0 -51.0
<b>Viscosity, Gardner 25°C</b>	W - Y
<b>Color, Gardner</b>	10 max.
<b>Acid value on solution, mgKOH/g</b>	10.0 - 17.0
<b>Type of oil</b>	Linseed / Tung
<b>Oil Length, %</b>	31
<b>Solvent</b>	Xylene

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for ALUKIDIR M-2168-50.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210610

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.