

Solventborne **High solids**

Product name
BECKOLITE AS-015

Description

BECKOLITE AS-015 is a solventborne saturated polyester resin to use in combination with amino resins for stoving enamels. It has excellent MEK resistance and hardness and flexibility balance. It is recommended for architectural, consumer electronics and home appliances coil coatings.

Applications

Architectural coil coating primers and topcoats.
Consumer electronics and home appliances coil coating primers and topcoats.

Key features

High-solids.
MEK resistance.
Hardness and flexibility.
Tin-free.

Characteristics

	BECKOLITE AS-015
Appearance	Clear liquid
Solids content, weight %	65.0 - 67.0
Viscosity, Gardner 25°C	V - Z1
Color, Gardner	3 max.
Acid value on solution, mgKOH/g	4.0 - 8.0
OH value on solids, mgKOH/g	Approx. 100
Solvent	Xylene / Butyl cellosolve

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for BECKOLITE AS-015.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.