

**Solventborne**

**Product name**

**BECKOLITE SD-401**

**Description**

BECKOLITE SD-401 is a solventborne saturated polyester resin to use in combination with amino resins for stoving enamels. BECKOLITE SD-401 has high gloss and excellent hardness and anti-corrosion properties. It is recommended for automotive, can and coil coatings.

**Applications**

Automotive surfacer.  
Can coatings.  
Coil coatings.

**Key features**

Hardness.  
High gloss.  
Anti-corrosion.  
Adhesion.

**Characteristics**

	<b>BECKOLITE SD-401</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	59.0 - 61.0
<b>Viscosity, Gardner 25°C</b>	R - U
<b>Color, Gardner</b>	2 max.
<b>Acid value on solution, mgKOH/g</b>	3.0 - 7.0
<b>Specific gravity, 25°C</b>	1.02 - 1.04
<b>Solvent</b>	Xylene / Butyl cellosolve

**Storage**

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

**Safe handling note**

Refer to SDS for BECKOLITE SD-401.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.