

Waterborne

Product name
BURNOCK WD-562

Description

BURNOCK WD-562 is a waterborne OH functional acrylic dispersion to use in combination with polyisocyanates for 2K polyurethane coatings for plastic applications. BURNOCK WD-562 has excellent adhesion to plastics and chemical resistance. It is recommended for consumer electronics and automotive interior coatings.

Applications

Consumer electronics.
Automotive interior coatings.

Key features

Adhesion to plastics.
MEK and chemical resistance.
Diethylene glycol dimethyl ether (MDM) free.

Characteristics

	BURNOCK WD-562
Appearance	Milky white liquid
Solids content, weight %	38.0 - 41.0
Viscosity, mPa s 25°C	10 - 3000
OH value on solids, mgKOH/g	Approx. 90
pH	7.0 - 8.5
Solvent	Propylene glycol butyl ether / Solvesso-100 / Water

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for BURNOCK WD-562.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210609

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.