

Solventborne

Product name
BURNOCK AC 2520

Description

BURNOCK AC 2520 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. BURNOCK AC 2520 has excellent mechanical and chemical resistance. It is recommended for different industrial and automotive refinishing applications.

Applications

Automotive exterior coatings.
Pigmented and clear topcoats.
Metallic basecoats.
General industrial coatings.
Wood coatings.

Key features

Flexibility.
Hardness and scratch resistance.
Chemical and mechanical resistance.
Pigment wetting.
High gloss.
Anti-corrosion.
Compatible with melamine resins.

Characteristics

	BURNOCK AC 2520
Appearance	Clear liquid
Solids content, weight %	58.0 - 62.0
Viscosity, Gardner 25°C	Y - Z3
Color, mg iodine	1 max.
Acid value on solids, mgKOH/g	10.0 max.
OH content on solids, %	4.0 - 5.0
Solvent	Xylene / Solvesso-100 / Butyl acetate

Storage

Store in a cool, dry, well-ventilated place at temperatures below 30°C.

Safe handling note

Refer to SDS for BURNOCK AC 2520.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.