

**Waterborne**

**Product name**  
**CERANATE WSA-1080**

**Description**

CERANATE WSA-1080 is a waterborne polysiloxane-acrylic hybrid resin to be cured with epoxy silane for 2K coatings. CERANATE WSA-1080 has excellent weather resistance and good adhesion to several substrates like metals, glass and plastics. It is recommended for exterior coatings.

**Applications**

Architectural exterior coatings.  
Infrastructure coatings.

**Key features**

Weather resistance.  
Anti-staining.  
Adhesion to several substrates like metals, glass and plastics.  
HAPS-free

**Characteristics**

	<b>CERANATE WSA-1080</b>
<b>Appearance</b>	Milky white liquid
<b>Solids content, weight %</b>	39.0 - 41.0
<b>Viscosity, mPa s 25°C</b>	20 - 500
<b>pH</b>	7.5 - 8.5
<b>MFFT, °C</b>	30 max.
<b>Solvent</b>	Water / Isopropyl alcohol / Dimethylethanolamine / Dipropylene glycol butyl ether

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for CERANATE WSA-1080.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210607

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.