

**Non-solvent**

**Product name**  
**EPICLON 860**

**Description**

EPICLON 860 is a semi-solid Bisphenol A type epoxy resin to use in combination with polyamines or polyamides for 2K coatings. EPICLON 860 has excellent anticorrosion, adhesion and fast curing properties. It is recommended for metal coatings.

**Applications**

Primer for metal and protective coatings.

**Key features**

- Semi-solid at room temperature.
- Anti-corrosion.
- Fast curing.
- Adhesion.

**Characteristics**

	<b>EPICLON 860</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	99.0 min.
<b>Viscosity, Gardner 25°C (70% in Diglyme)</b>	P - U
<b>Epoxy equivalent weight on solids, g/eq</b>	235 - 255

**Storage**

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

**Safe handling note**

Refer to SDS for EPICLON 860.  
 Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.