TECHNICAL DATA SHEET



Solventborne

Product name EPICLON P-439

Description

EPICLON P-439 is a solventborne 1K epoxy resin for metal coatings. EPICLON P-439 has excellent adhesion to metals and hardness. It is recommended for protective coatings.

Applications

Protective coatings.

Key features

Adhesion to metals. Hardness.

Characteristics

| | EPICLON P-439 |
|--------------------------|---------------------------------------|
| Appearance | Clear liquid |
| Solids content, weight % | 38.0 - 42.0 |
| Viscosity, Gardner 25°C | U - Y |
| Solvent | Xylene / n-Butanol / Butyl cellosolve |

Storage

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for EPICLON P-439. Please confirm with our sales representative regarding chemical regulatory status of intended countries.

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.