TECHNICAL DATA SHEET



Powder

Product name FINEDIC A-251

Description

FINEDIC A-251 is a OH functional powder acrylic resin compatible with polyester powder coatings. FINEDIC A-251 can be used as an additive to reduce pinholes in powder polyester coatings.

Applications

Additive in powder polyester coatings

Key features

Recommended in powder polyester coating systems. Eliminates pinholes.

Characteristics

	FINEDIC A-251	
Appearance	Clear granules	
Solids content, weight %	99.0 min.	
Color, Gardner 60% in Xylene	1 max.	
OH value on solids, mgKOH/g	95 - 115	
Softening point, °C Ring & Ball	105 - 115	
Melt index, g/10 min 125°C	8.0 - 28.0	

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for FINEDIC A-251. Please confirm with our sales representative regarding chemical regulatory status of intended countries.

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.