

**Powder**

**Product name**  
**FINEPLUS AC 2710**

**Description**

FINEPLUS AC 2710 is a powder glycidyl methacrylate (GMA) functional acrylic resin. FINEPLUS AC 2710 has excellent flow, levelling and gloss. It is recommended as powder acrylic coating for exterior clear-coat applications.

**Applications**

Automotive exterior coatings.  
 Home appliances.  
 Architectural metal coatings.

**Key features**

Weather resistance.  
 Film smoothness.  
 Clarity.

**Characteristics**

	<b>FINEPLUS AC 2710</b>
<b>Appearance</b>	Hazy granules
<b>Solid content, weight %</b>	99.5 min.
<b>Color, Hazen 30% in Xylene</b>	10 max.
<b>Epoxy equivalent weight, g/eq</b>	300 - 350
<b>Melt index</b>	100 - 120
<b>Insoluble substances, mg/g</b>	0.005 max.

**Storage**

Store in a cool, dry, well-ventilated place at temperatures below 15°C.

**Safe handling note**

Refer to SDS for FINEPLUS AC 2710.  
 Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.