

**Solventborne** **High solids**

**Product name**  
**Idecryl-2573**

**Description**

Idecryl-2573 is a solventborne OH functional acrylic resin that can be used in combination with amino resins for stoving enamels or with polyisocyanates for 2K polyurethane coatings. Idecryl-2573 has excellent weather resistance. It is recommended for automotive refinishing base and topcoats and industrial coatings.

**Applications**

Automotive refinishing.  
General industrial coatings.

**Key features**

Weather resistance.

**Characteristics**

	<b>Idecryl-2573</b>
<b>Appearance</b>	Clear liquid
<b>Solids content, weight %</b>	68.0 - 72.0
<b>Viscosity, Gardner 25°C</b>	Z3 - Z4
<b>Color, Gardner</b>	1 max.
<b>Acid value on solids, mgKOH/g</b>	8 max.
<b>OH value on solids, mgKOH/g</b>	68 - 72
<b>OH content on solids, %</b>	2.1 - 2.2
<b>Solvent</b>	Xylene

**Storage**

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

**Safe handling note**

Refer to SDS for Idecryl-2573.  
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.