

Solventborne

Product name
Idecryl-8062

Description

Idecryl-8062 is a solventborne OH functional acrylic resin to use in combination with polyisocyanates for 2K polyurethane coatings. Idecryl-8062 has fast drying properties and excellent adhesion to metal substrates. It is recommended for a wide range of applications like automotive, wood or direct to metal (DTM) coatings.

Applications

Automotive coatings.
Wood coatings.
Floor coatings.
Industrial coatings.
Direct to metal (DTM) coatings.

Key features

Fast drying.
Weather resistance.

Characteristics

	Idecryl-8062
Appearance	Clear liquid
Solids content, weight %	53.0 - 57.0
Viscosity, mPa s 25°C	2000 - 3000
Color, Gardner	1 max.
Acid value on solids, mgKOH/g	5 max.
OH value on solids, mgKOH/g	48 - 50
OH content on solids, %	1.4 -1.5
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for Idecryl-8062.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220519

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.