

Solventborne **High solids**

Product name
Idecryl-8064

Description

Idecryl-8064 is a solventborne OH functional acrylic resin. Idecryl-8064 has high gloss and excellent appearance. It is recommended for automotive refinishing topcoats and wood coatings.

Applications

Automotive refinishing.
 General industrial coatings.

Key features

High gloss.
 Weather resistance.
 Can be cured at ambient temperatures using polyisocyanates and at elevated temperatures using butylated melamine resins.

Characteristics

	Idecryl-8064
Appearance	Clear liquid
Solids content, weight %	68.0 - 72.0
Viscosity, Ford cup#4 seconds 30°C (76.9% resin solution in Butyl Acetate)	48 - 58
Color, Gardner	1 max.
Acid value on solids, mgKOH/g	5 max.
OH content on solids, %	2.9 - 3.2
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for Idecryl-8064.
 Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210603

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.