

Solventborne

Product name
Idehydrol-5069

Description

Idehydrol-5069 is a solventborne fatty acid modified polyurethane dispersion to use with metal carboxylate driers. Idehydrol-5069 has excellent anti-staining properties against hot coffee, tea, beer and mild alkali and acids. It is recommended for wood, metal, glass and leather coatings.

Applications

Wood coatings.
Metal coatings.
Glass coatings.
Leather coatings.

Key features

Anti-staining.

Characteristics

	Idehydrol-5069
Appearance	Milky white liquid
Solids content, weight%	35.0 - 37.0
Viscosity, Ford cup#4 seconds 30°C	20 - 40
OH value on solids, mgKOH/g	35 - 45
pH, 25°C	7.0 - 8.0
Neutralizer	Triethyl amine
Solvent	Water, N-Methyl-2-pyrrolidone

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for Idehydrol-5069.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.