

Solventborne**Product name****LUCKAMIDE 12-242****Description**

LUCKAMIDE 12-242 is a solventborne polyamide hardener for 2K ambient temperature curing epoxy coatings. LUCKAMIDE 12-242 has excellent anti-corrosion, adhesion and fast drying properties. It is recommended for heavy duty and marine coatings.

Applications

Marine coatings.
Protective coatings.
Metal coatings.
Architectural coatings.
Heavy duty.

Key features

Flexibility.
High gloss.
Adhesion.
Anti-corrosion.
Fast drying.

Characteristics

	LUCKAMIDE 12-242
Appearance	Clear liquid
Solids content, weight %	69.0 - 71.0
Viscosity, Gardner 25°C	X - Z1
Color, Gardner	9 max.
Amine value on solids, g/eq	160 - 200
Solvent	Toluene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for LUCKAMIDE 12-242.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220501

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC CorporationFor more information: <https://www.dic-global.com/en/products/coating.html>