

Solventborne

UV Curable

High solids

Product name

LUXYDIR ZHU-2145

Description

LUXYDIR ZHU-2145 is a solventborne urethane acrylate UV curable resin. LUXYDIR ZHU-2145 has excellent flexibility and adhesion properties. It is recommended for plastic films like PET, PVC or TAC.

Applications

Elastic films backcoat.
Film substrates coatings.

Key features

Flexibility.
Adhesion.
Elongation rate of the coating can reach 20% without cracking.

Characteristics

| | LUXYDIR ZHU-2145 |
|---------------------------------|------------------|
| Appearance | Clear liquid |
| Solids content, weight % | 74.0 - 76.0 |
| Viscosity, Gardner 25°C | U - V |
| Color, Gardner | 1 max. |
| Solvent | Butyl acetate |

Storage

Store in a cool, dry, well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for LUXYDIR ZHU-2145.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

210607

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.