

UV Curable

Product name
LUXYDIR V-4025-ZS

Description

LUXYDIR V-4025-ZS is a solventborne UV curable resin. LUXYDIR V-4025-ZS has excellent yellowing resistance, hardness and abrasion resistance. It is recommended for plastic coatings and plastic parts.

Applications

Consumer electronics.
 Home appliances.
 Automotive interior coatings.

Key features

Leveling.
 Hardness.
 Abrasion resistance.

Characteristics

	LUXYDIR V-4025-ZS
Appearance	Clear liquid
Solids content, weight %	78.0 - 82.0
Viscosity, Gardner 25°C	0 - U
Color, Gardner	1 max.
Solvent	Butyl acetate

Storage

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for LUXYDIR V-4025-ZS.
 Please confirm with our sales representative regarding chemical regulatory status of intended countries.

211101

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.