

TECHNICAL DATA SHEET

Non-solvent

UV Curable

Product name

LUXYDIR V-4221

Description

LUXYDIR V-4221 is a solvent free urethane acrylate UV curable resin. LUXYDIR V-4221 has excellent adhesion to plastic substrates and film elongation. It is recommended for soft type coatings.

Applications

Wood coatings.

Physical vapor deposition basecoats.

Soft coatings.

Key features

Adhesion to plastics substrates.

Flexibility.

Characteristics

| | LUXYDIR V-4221 |
|---|----------------|
| Appearance | Clear liquid |
| Solids content, weight% | 100 |
| Viscosity, Gardner 25°C (70% in Butyl acetate) | U - X |
| Color, Gardner | 1 max. |

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for LUXYDIR V-4221.

Please confirm with our sales representative regarding chemical regulatory status of intended countries.

220318

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC Corporation

For more information: <https://www.dic-global.com/en/products/coating.html>