

Waterborne

UV Curable

Product name

WATERSOL V-204

Description

WATERSOL V-204 is a waterborne UV curable resin. WATERSOL V-204 has excellent adhesion to plastics, leveling and workability properties. It is recommended for vacuum electroplating primers.

Applications

Home appliances.
Consumer electronics.
Automotive interior coatings.
Cosmetics packaging.

Key features

Adhesion to plastic substrates.
Leveling.
Adhesion with electrodeposition layer.
Workability.

Characteristics

	WATERSOL V-204
Appearance	Milky yellowish liquid
Solids content, weight %	39.0 - 41.0
Viscosity, mPa s 25°C	300 - 3000
pH	7.0 - 9.0
Solvent	Water / Dipropylene glycol dimethyl ether

Storage

Store in a cool, dry, and well-ventilated place at temperatures below 25°C.

Safe handling note

Refer to SDS for WATERSOL V-204.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

211101

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.

DIC Corporation

For more information: <https://www.dic-global.com/en/products/coating.html>