

Waterborne

UV Curable

Product name

WATERSOL V-206 (Lab sample)

Description

WATERSOL V-206 is a waterborne UV curable resin. WATERSOL V-206 has adhesion to plastic substrates, excellent water resistance, high hardness and abrasion resistance. It is recommended for home appliances, consumer electronics, and automotive interior coatings.

Applications

Home appliance.
Consumer electronics.
Automotive interior coatings.

Key features

Water resistance.
Hardness.
Abrasion resistance.

Characteristics

	WATERSOL V-206
Appearance	Milky white liquid
Solids content, weight %	39.0 - 41.0
Viscosity, mPa s, 25°C	5 - 200
pH	6.5 - 9.0
Solvent	Water, Dipropylene glycol dimethyl ether

Storage

Store in a cool, dry, well-ventilated place at temperature below 25°C.

Safe handling note

Refer to SDS for WATERSOL V-206.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

231111

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.