

Solventborne

Product name
Idecryl-7892

Description

Idecryl-7892 is a solventborne thermoplastic acrylic resin to use for 1K, room temperature curing coatings. Idecryl-7892 has fast drying. It is recommended for clear or pigmented coatings for plastic (ABS, HIPS, etc.), metal (specifically galvanized substrate), and concrete surfaces. It can also be used for clear coatings over water based textured coatings.

Applications

Plastic coatings.
Metal coatings.

Key features

Fast drying.

Characteristics

	Idecryl-7892
Appearance	Clear liquid
Solids content, weight %	48.0 - 52.0
Viscosity, Gardner 25°C	X - Z
Color, Gardner	1 max.
Acid value on solids, mgKOH/g	5.0 max.
Solvent	Xylene

Storage

Store in a cool, dry, and well-ventilated place as mentioned in SDS.

Safe handling note

Refer to SDS for Idecryl-7892.
Please confirm with our sales representative regarding chemical regulatory status of intended countries.

240219

All information on this data sheet is based on DIC Corporation laboratory tests and characteristics shown here are not sales specifications. Procedures and directions for use of DIC Corporation products are recommendations only, with no warranties expressed or implied. The user is solely responsible for determining suitability of DIC Corporation products for the particular application. DIC Corporation recommends consultation with its technical experts and trials before general or production use of any of its products. DIC Corporation products are provided subject to its standard terms and conditions. This data sheet supersedes all previous publications for the products described herein.